Steel, High Strength, F1554, ASTM A193, Stainless, Exotics



MILD STEEL

LOW-STRENGTH / MILD STEEL

			50,00	- STRENGTH 0 psi	/ MILD S	TEEL	
2-56	LENGTH "	2-56 STEEL PLAIN	2-56 STEEL ZINC	2-56 STEEL H.D.G.	2-56 BRASS	2-56 NYLON	2-56 ALUMINUM
	36" (3 FT)		-	-	2C3600RODB	-	-
4.40		4-40 STEEL	4-40 STEEL	4-40 STEEL	4-40	4-40	4-40
4-40	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT) 48" (4 FT)	4C3600RODXU -	4C3600RODXZ	-	4C3600RODB -	- 4C4800RODN	-
F 40		5-40 STEEL	5-40 STEEL	5-40 STEEL	5-40	5-40	5-40
5-40	1ENGTH " 36" (3 FT)	PLAIN -	ZINC 5C3600RODXZ	H.D.G.	BRASS	NYLON -	ALUMINUM -
	30 (3 F1)	•	3C3000KODX2				-
6-32		6-32 STEEL	6-32 STEEL	6-32 STEEL	6-32	6-32	6-32
0-32	1 LENGTH " 36" (3 FT)	PLAIN -	ZINC 6C3600RODXZ	H.D.G.	BRASS 6C3600RODB	NYLON -	ALUMINUM
	()						
8-32		8-32 STEEL	8-32 STEEL	8-32 STEEL	8-32	8-32	8-32
0 02	1ENGTH " 36" (3 FT)	PLAIN 8C3600RODXU	ZINC 8C3600RODXZ	H.D.G.	BRASS 8C3600RODB	NYLON -	ALUMINUM 8C3600RODA
10-24		10-24 STEEL	10-24 STEEL	10-24 STEEL	10-24	10-24	10-24
10-24	LENGTH " 24" (2 FT)	PLAIN -	ZINC 10C2400RODXZ	H.D.G.	BRASS -	NYLON -	ALUMINUM -
	36" (3 FT) 48" (4 FT)	-	10C3600RODXZ		10C3600RODB	- 10C4800RODN	10C3600RODA
	72" (6 FT)		10C7200RODXZ		-	-	10C7200RODA
10-32		10-32 STEEL	10-32 STEEL	10-32 STEEL	10-32	10-32	10-32
10-32	36" (3 FT)	PLAIN -	ZINC 10F3600RODXZ	H.D.G.	BRASS 10F3600RODB	NYLON -	ALUMINUM 10F3600RODA
	48" (4 FT)					10F4800RODN	-
12-24		12-24 STEEL	12-24 STEEL	12-24 STEEL	12-24	12-24	12-24
12-24	LENGTH " 36" (3 FT)	PLAIN -	ZINC 12C3600RODXZ	H.D.G.	BRASS	NYLON -	ALUMINUM
	30 (311)		120300000000	_		-	-
1/4 20		1/4-20 STEEL	1/4-20 STEEL	1/4-20 STEEL	1/4-20	1/4-20	1/4-20
1/4-20	LENGTH " 8"	PLAIN	ZINC 25C800RODXZ	H.D.G.	BRASS	NYLON	ALUMINUM
	8 1/2"	-	25C850RODXZ	-	-	-	-
	9 1/2"	-	25C950RODXZ 25C1000RODXZ	-	-	-	-
	11" 12" (1 FT)	-	25C1100RODXZ 25C1200RODXZ		-		
	13" 24" (2 FT)		25C1300RODXZ 25C2400RODXZ		-		-
	36" (3 FT)	25C3600RODXU	25C3600RODXZ	-	25C3600RODB		25C3600RODA
	48" (4 FT) 60" (5 FT)	25C4800RODXU -	- 25C6000RODXZ	-	-	25C4800RODN -	-
	72" (6 FT) 120" (10 FT)	25C7200RODXU 25C12000RODXU	25C7200RODXZ 25C12000RODXZ	-	-		25C7200RODA
	144" (12 FT)	25C14400RODXU	25C14400RODXZ		-	-	-
1/4-28	LENGTH "	1/4-28 STEEL PLAIN	1/4-28 STEEL ZINC	1/4-28 STEEL H.D.G.	1/4-28 BRASS	1/4-28 NYLON	1/4-28 ALUMINUM
	36" (3 FT) 144" (12 FT)	- 25F14400RODXU	25F3600RODXZ	-	25F3600RODB	-	-
	144 (1211)	23F14400RODAO		_		-	
5/16-18		5/16-18 STEEL	5/16-18 STEEL	5/16-18 STEEL	5/16-18	5/16-18	5/16-18
0/ 10-10	LENGTH " 12" (1 FT)	PLAIN -	ZINC 31C1200RODXZ	H.D.G.	BRASS	NYLON -	ALUMINUM -
	36" (3 FT) 48" (4 FT)	31C3600RODXU	31C3600RODXZ	-	31C3600RODB	- 31C4800RODN	31C3600RODA
	72" (6 FT)	-	31C7200RODXZ	-	-	-	31C7200RODA
	120" (10 FT) 144" (12 FT)	31C12000RODXU 31C14400RODXU	31C12000RODXZ 31C14400RODXZ	-	-	-	-
5/16-24	LENGTH "	5/16-24 STEEL PLAIN	5/16-24 STEEL ZINC	5/16-24 STEEL H.D.G.	5/16-24 BRASS	5/16-24 NYLON	5/16-24 ALUMINUM
	36" (3 FT)	-	31F3600RODXZ	-	31F3600RODB	-	-
3/8-16	LENGTH "	3/8-16 STEEL PLAIN	3/8-16 STEEL ZINC	3/8-16 STEEL H.D.G.	3/8-16 BRASS	3/8-16 NYLON	3/8-16 ALUMINUM
	4" 8 1/2"	-	37C400RODXZ 37C850RODXZ	- :	-	-	-
	9"	-	37C900RODXZ	-	-	-	-
	9 1/2" 12" (1 FT)	-	37C950RODXZ 37C1200RODXZ	-	-	-	-
	24" (2 FT) 36" (3 FT)	- 37C3600RODXU	37C2400RODXZ 37C3600RODXZ	- 37C3600RODXG	- 37C3600RODB	-	- 37C3600RODA
	48" (4 FT)	-	-	-	-	37C4800RODN	-
	72" (6 FT) 120" (10 FT)	- 37C12000RODXU	37C7200RODXZ 37C12000RODXZ	- 37C12000RODXG	-	-	37C7200RODA -
	144" (12 FT)	37C14400RODXU	37C14400RODXZ	-	-	-	-
3/8-24	LENGTHE	3/8-24 STEEL	3/8-24 STEEL	3/8-24 STEEL	3/8-24	3/8-24	3/8-24
-	36" (3 FT)	PLAIN 37F3600RODXU	ZINC 37F3600RODXZ	H.D.G.	BRASS 37F3600RODB	NYLON -	ALUMINUM -
	72" (6 FT) 120" (10 FT)	37F7200RODXU -	37F7200RODXZ 37F12000RODXZ	-	-	-	-
7/40 44	- 1	7/16-14 STEEL	7/16-14 STEEL	7/16-14 STEEL	7/16-14	7/16-14	7/16-14
7/16-14	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT) 72" (6 FT)	43C3600RODXU 43C7200RODXU	43C3600RODXZ 43C7200RODXZ	-	43C3600RODB -	-	43C3600RODA -
	120" (10 FT) 144" (12 FT)	43C12000RODXU 43C14400RODXU	43C12000RODXZ 43C14400RODXZ	-	-	-	-
	,/						



MILD STEEL

LOW-STRENGTH / MILD STEEL

50,000 psi

	7/16-20 STEEL	7/16-20 STEEL	7/16-20 STEEL	7/16-20	7/16-20	7/16-20
LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
36" (3 FT)	43F3600RODXU	43F3600RODXZ				
72" (6 FT)	43F7200RODXU	-	-	-	-	-
	36" (3 FT)	LENGTH " PLAIN 36" (3 FT) 43F3600RODXU	LENGTH " PLAIN ZINC 36" (3 FT) 43F3600RODXU 43F3600RODXZ	LENGTH " PLAIN ZINC H.D.G. 36" (3 FT) 43F3600RODXU 43F3600RODXZ -	LENGTH " PLAIN ZINC H.D.G. BRASS 36" (3 FT) 43F3600RODXU 43F3600RODXZ - -	LENGTH " PLAIN ZINC H.D.G. BRASS NYLON 36" (3 FT) 43F3600RODXU 43F3600RODXZ - - -

4 /0 43		1/2-13 STEEL	1/2-13 STEEL	1/2-13 STEEL	1/2-13	1/2-13	1/2-13
1/2-13	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	6"	-	50C600RODXZ		-	-	
	7"		50C700RODXZ		-		
	12" (1 FT)	-	50C1200RODXZ	50C1200RODXG	-		-
	36" (3 FT)	50C3600RODXU	50C3600RODXZ	50C3600RODXG	50C3600RODB	-	50C3600RODA
	48" (4 FT)	-	-		-	50C4800RODN	
	72" (6 FT)	50C7200RODXU	50C7200RODXZ		50C7200RODB	-	50C7200RODA
	120" (10 FT)	50C12000RODXU	50C12000RODXZ	50C12000RODXG	-	-	-
	144" (12 FT)	50C14400RODXU	50C14400RODXZ	50C14400RODXG	-	-	-

1/2-20	LENGTH "	1/2-20 STEEL PLAIN	1/2-20 STEEL ZINC	1/2-20 STEEL H.D.G.	1/2-20 BRASS	1/2-20 NYLON	1/2-20 ALUMINUM
	36" (3 FT)	50F3600RODXU	50F3600RODX7				

9/16-12		9/16-12 STEEL	9/16-12 STEEL	9/16-12 STEEL	9/16-12	9/16-12	9/16-12
3/ 10-12	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	56C3600RODXU	56C3600RODXZ		-	-	-
	72" (6 FT)		56C7200RODXZ				-
	120" (10 FT)	-	56C12000RODXZ	-	-	-	-
	144" (12 FT)	56C14400RODXU					-

9/16-18	LENGTH "	9/16-18 STEEL PLAIN	9/16-18 STEEL ZINC	9/16-18 STEEL H.D.G.	9/16-18 BRASS	9/16-18 NYLON	9/16-18 ALUMINUM	
	36" (3 FT)	56F3600RODXU	56F3600RODXZ		-	-	-	
	72" (6 FT)	56F7200RODXU			-		-	

5/8-11		5/8-11 STEEL	5/8-11 STEEL	5/8-11 STEEL	5/8-11	5/8-11	5/8-11
0/0-11	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	24" (2 FT)	-	62C2400RODXZ	-	-	-	-
	36" (3 FT)	62C3600RODXU	62C3600RODXZ	62C3600RODXG	62C3600RODB	-	62C3600RODA
	48" (4 FT)	62C4800RODXU	-		-	62C4800RODN	-
	72" (6 FT)	62C7200RODXU	62C7200RODXZ	-	-	-	62C7200RODA
	120" (10 FT)	62C12000RODXU	62C12000RODXZ	62C12000RODXG	-	-	-
	144" (12 FT)	62C14400RODXU	-		-		-

5/8-18	LENGTH "	5/8-18 STEEL PLAIN	5/8-18 STEEL ZINC	5/8-18 STEEL H.D.G.	5/8-18 BRASS	5/8-18 NYLON	5/8-18 ALUMINUM
	36" (3 FT)	62F3600RODXU	62F3600RODXZ	-	-	-	-
	144" (12 FT)	62F14400RODXU	62F14400RODXZ	-	-	-	-

3/4-10		3/4-10 STEEL	3/4-10 STEEL	3/4-10 STEEL	3/4-10	3/4-10	3/4-10
3/ 4-10	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	75C3600RODXU	75C3600RODXZ	75C3600RODXG	-	-	75C3600RODA
	48" (4 FT)		-	-	-	75C4800RODN	-
	72" (6 FT)	75C7200RODXU	75C7200RODXZ	75C7200RODXG	75C7200RODB	-	-
	120" (10 FT)	75C12000RODXU	75C12000RODXZ	75C12000RODXG	-	-	-
	1 4 4 H (1 2 FT)	7F C1 4400D O D VI I	7FC1 4400DODY7	7FC14400D0DVC			

3/4-16		3/4-16 STEEL	3/4-16 STEEL	3/4-16 STEEL	3/4-16	3/4-16	3/4-16
3/4-10	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 ET)		75E3600PODY7	_	_	_	

7/8-9		7/8-9 STEEL	7/8-9 STEEL	7/8-9 STEEL	7/8-9	7/8-9	7/8-9
1/0-3	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	-	87C3600RODXZ	87C3600RODXG	87C3600RODB	-	87C3600RODA
	120" (10 FT)	87C12000RODXU	87C12000RODXZ	87C12000RODXG	-		-
	144" (12 FT)	-	87C14400RODXZ	-	-	-	-





MILD STEEL

LOW-STRENGTH / MILD STEEL

50,000 psi

36"(3 FT) - 87F3600RODXZ - 87F3600RODB -	JB

L"-8		1"-8 STEEL	1"-8 STEEL	1"-8 STEEL	1"-8	1"-8	1"-8
r -0	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	24" (2 FT)		100C2400RODXZ	-	-	-	-
	36" (3 FT)	100C3600RODXU	100C3600RODXZ	100C3600RODXG	-	-	100C3600RODA
	72" (6 FT)	100C7200RODXU	100C7200RODXZ	100C7200RODXG	-	-	-
	120" (10 FT)	100C12000RODXU	100C12000RODXZ	100C12000RODXG	-		
	144" (12 FT)	100C14400RODXZ	100C14400RODXU	100C14400RODXG	-		

1"-14		1"-14 STEEL	1"-14 STEEL	1"-14 STEEL	1"-14	1"-14	1"-14
1 -14	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	100F3600RODXU	100F3600RODXZ	-	-	-	-
	144" (12 FT)	100F14400RODXII					

1-1/8-7		1-1/8-7 STEEL	1-1/8-7 STEEL	1-1/8-7 STEEL	1-1/8-7	1-1/8-7	1-1/8-7
1-1/0-1	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	112C3600RODXU	112C3600RODXZ	-	-	-	-
	72" (6 FT)	112C7200RODXU	112C7200RODXZ	-	-		-
	120" (10 FT)	112C12000RODXU	112C12000RODXZ	112C12000RODXG	-	-	-
	144" (12 FT)	112C14400RODXII	112C14400RODX7	112C14400RODXG			

1-1/8-12		1-1/8-12 STEEL	1-1/8-12 STEEL	1-1/8-12 STEEL	1-1/8-12	1-1/8-12	1-1/8-12
1-1/0-12	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)		112F3600RODXZ		-	-	
	1201 (10 FT)	11251200000000					

1-1/4-7		1-1/4-7 STEEL	1-1/4-7 STEEL	1-1/4-7 STEEL	1-1/4-7	1-1/4-7	1-1/4-7
1-1/4-1	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	125C3600RODXU	125C3600RODXZ		-	-	-
	72" (6 FT)	-	125C7200RODXZ	-	-	-	-
	120" (10 FT)	125C12000RODXU	125C12000RODXZ	125C12000RODXG			-
	144" (12 FT)	125C14400RODXU	125C14400RODXZ	125C14400RODXG			

1-1/4-12		1-1/4-12 STEEL	1-1/4-12 STEEL	1-1/4-12 STEEL	1-1/4-12	1-1/4-12	1-1/4-12
/	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	125F3600RODXU	125F3600RODXZ		-	-	-
	120" (10 FT)	125F12000RODXU			-	-	-
	144" (12 FT)	125F14400RODXII					

1-3/8-6		1-3/8-6 STEEL	1-3/8-6 STEEL	1-3/8-6 STEEL	1-3/8-6	1-3/8-6	1-3/8-6
1-3/8-6	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	137C3600RODXU	137C3600RODXZ	-	-	-	-
	72" (6 FT)		137C7200RODXZ			-	

1-1/2-6		1-1/2-6 STEEL	1-1/2-6 STEEL	1-1/2-6 STEEL	1-1/2-6	1-1/2-6	1-1/2-6
1-1/2-0	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	150C3600RODXU	150C3600RODXZ	-	-	-	-
	72" (6 FT)	150C7200RODXU	150C7200RODXZ	-	-	-	-
	120" (10 FT)		150C12000RODXZ	-	-	-	-
	144" (12 ET)	150C14400PODVII	150C14400PODY7	150C14400PODYG	_		-

4 4 /0 40		1-1/2-12 STEEL	1-1/2-12 STEEL	1-1/2-12 STEEL	1-1/2-12	1-1/2-12	1-1/2-12
1-1/2-12	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	36" (3 FT)	-	150F3600RODXZ	-	-	-	-

1-3/4-5	LENGTH "	1-3/4-5 STEEL PLAIN	1-3/4-5 STEEL ZINC	1-3/4-5 STEEL H.D.G.	1-3/4-5 BRASS	1-3/4-5 NYLON	1-3/4-5 ALUMINUM
	36" (3 FT)	-	175C3600RODXZ	-	-	-	-
	72" (6 FT)	175C7200RODXU	-	-		-	-
	144" (12 FT)	175C14400RODXU	-	-		-	-

0" 4 E		2"-4.5 STEEL	2"-4.5 STEEL	2"-4.5 STEEL	2"-4.5	2"-4.5	2"-4.5
2"-4.5	LENGTH "	PLAIN	ZINC	H.D.G.	BRASS	NYLON	ALUMINUM
	144" (12 FT)	200C14400RODXII					





THREADED ROD

HIGH-STRENGTH



HIGH-STRENGTH / ASTM A354BD 150,000 psi PLAIN

3/8-16		3/8-16 PLAIN
, 0-10	LENGTH "	ASTM A354-BD
	36" (3 FT)	37C3600RODXU/A354-BD

1-1/8-7		1-1/8-7 PLAIN
1-1/0-1	LENGTH "	ASTM A354-BD
	36" (3 FT)	112C3600RODXU/A354-B

7/16-14	LENGTH "	7/16-14 PLAIN ASTM A354-BD
	36" (3 FT)	43C3600RODXU/A354-BD

1-1/4-7		1-1/4-7 PLAIN
/	LENGTH "	ASTM A354-BD
	36" (3 FT)	125C3600RODXII/A354-RD

1/2-13		1/2-13 PLAIN
_/	LENGTH "	ASTM A354-BD
	36" (3 FT)	50C3600RODXU/A354-BD
72" (6 FT)		50C7200RODXU/A354-BD
	144" (12 FT)	50C14400RODXU/A354-BD

1/2-20	LENGTH "	1/2-20 PLAIN ASTM A354-BD
	36" (3 FT)	50F3600RODXU/A354-BD

5/8-11		5/8-11 PLAIN
-/	LENGTH "	ASTM A354-BD
	36" (3 FT)	62C3600RODXU/A354-BD
	72" (6 FT)	62C7200RODXU/A354-BD

5/8-18		5/8-18 PLAIN
-,	LENGTH "	ASTM A354-BD
	72" (6 FT)	62F7200ROD/A354-BD

3/4-10		3/4-10 PLAIN
-/	LENGTH "	ASTM A354-BD
	36" (3 FT)	75C3600RODXU/A354-BD







HIGH-STRENGTH / ASTM A354BD



ASTM F1554 ANCHOR BOLTS [Grade 36, Grade 55, Grade 105]

F1554 Grade 36	Low Carbon, 36 ksi yield steel anchor bolts.
F1554 Grade 55	High Strength, Low Alloy, 55 ksi yield steel anchor bolts.
F1554 Grade 105	Allov, Heat Treated, High Strength, 105 ksi vield steel anchor bolts.

1 /0 40		1/2-13 STEEL PLAIN	1/2-13 STEEL ZINC	1/2-13 STEEL H.D.G.	1/2-13 STEEL PLAIN	1/2-13 STEEL H.D.G.	1/2-13 STEEL PLAIN
1/2-13	LENGTH "	F1554-GR36	F1554-GR36	F1554-GR36	F1554-GR55	F1554-GR55	F1554-GR105
	36" (3 FT)			50C3600RODXG/F1554-36	-	-	
	72" (6 FT)			50C7200RODXG/F1554-36	-		50C7200RODXU/F1554-105
	120" (10 FT)	-	50C12000RODXZ/F1554-36	50C12000RODXG/F1554-36	-	-	-
	144" (12 FT)		50C14400RODXZ/F1554-36	50C14400RODXG/F1554-36			

5/8-11	LENGTH "	5/8-11 STEEL PLAIN F1554-GR36	5/8-11 STEEL ZINC F1554-GR36	5/8-11 STEEL H.D.G. F1554-GR36	5/8-11 STEEL PLAIN F1554-GR55	5/8-11 STEEL H.D.G. F1554-GR55	5/8-11 STEEL PLAIN F1554-GR105
	36" (3 FT)			62C3600RODXG/F1554-36			
	72" (6 FT)		•		62C7200RODXU/F1554-55		-
	120" (10 FT)	62C12000RODXU/F1554-36	62C12000RODXZ/F1554-36	62C12000RODXG/F1554-36	-		
	144" (12 FT)		62C14400RODXZ/F1554-36	62C14400RODXG/F1554-36	-	62C14400RODXG/F1554-55	-

3/4-10	LENGTH "	3/4-10 STEEL PLAIN F1554-GR36	3/4-10 STEEL ZINC F1554-GR36	3/4-10 STEEL H.D.G. F1554-GR36	3/4-10 STEEL PLAIN F1554-GR55	3/4-10 STEEL H.D.G. F1554-GR55	3/4-10 STEEL PLAIN F1554-GR105
-,	LENGIH	F1334-GR30	F1554-GR30	F1334-GR30	F1334-GK33	F1334-GK33	F1554-GK105
	36" (3 FT)	75C3600RODXU/F1554-36	-	-	-	-	-
	72" (6 FT)	75C7200RODX/1554-G36			75C7200RODXU/F1554-G55	75C7200RODXG/F1554-36-D	
	120" (10 FT)	75C12000RODXU/F1554-36	75C12000RODXZ/F1554-36	75C12000RODXG/F1554-36	-		
	144" (12 FT)	75C14400RODXU/F1554-36	75C14400RODXZ/F1554-36	75C14400RODXG/F1554-36	75C14400RODXU/F1554-55		75C14400RODXU/1554-105

7/8-9	LENGTH "	7/8-9 STEEL PLAIN F1554-GR36	7/8-9 STEEL ZINC F1554-GR36	7/8-9 STEEL H.D.G. F1554-GR36	7/8-9 STEEL PLAIN F1554-GR55	7/8-9 STEEL H.D.G. F1554-GR55	7/8-9 STEEL PLAIN F1554-GR105
	72" (6 FT)	87C7200RODXU/F1554-36		87C7200RODXG/F1554-36	87C7200RODXU/F1554-G55		-
	120" (10 FT)		87C12000RODXZ/F1554-36		-		
	144" (12 FT)	-	-	87C14400RODXG/F1554-36	87C1400RODXU/F1554-55	-	-

4 11 0		1"-8 STEEL PLAIN	1"-8 STEEL ZINC	1"-8 STEEL H.D.G.	1"-8 STEEL PLAIN	1"-8 STEEL H.D.G.	1"-8 STEEL PLAIN
1"-8	LENGTH "	F1554-GR36	F1554-GR36	F1554-GR36	F1554-GR55	F1554-GR55	F1554-GR105
	36" (3 FT)	100C3600RODXU/F1554-36		100C3600RODXG/F1554-36	100C3600RODXU/F1554-55		100C3600RODXU/F1554-105
	120" (10 FT)	100C12000RODXU/F1554-36		100C12000RODXG/F1554-36			100C12000RODXU/F1554-105-D
	144" (12 FT)	-	100C12000RODXZ/F1554-36	100C14400RODXG/F1554-36	100C14400RODXU/F1554-55	100C14400RODXG/F1554-55	-

1-1/8-7	LENGTH "	1-1/8-7 STEEL PLAIN F1554-GR36	1-1/8-7 STEEL ZINC F1554-GR36	1-1/8-7 STEEL H.D.G. F1554-GR36	1-1/8-7 STEEL PLAIN F1554-GR55	1-1/8-7 STEEL H.D.G. F1554-GR55	1-1/8-7 STEEL PLAIN F1554-GR105
/ -	36" (3 FT)			112C3600RODXG/F1554-36	-		
	144" (12 FT)	-	-	112C14400RODXG/F1554-36			-

4 4 /4 7		1-1/4-7 STEEL PLAIN	1-1/4-7 STEEL ZINC	1-1/4-7 STEEL H.D.G.	1-1/4-7 STEEL PLAIN	1-1/4-7 STEEL H.D.G.	1-1/4-7 STEEL PLAIN
1-1/4-7	LENGTH "	F1554-GR36	F1554-GR36	F1554-GR36	F1554-GR55	F1554-GR55	F1554-GR105
	144" (12 FT)		125C14400RODX7/E1554-36		125C14400RODXII/E1554-55	125C14400RODXG/E1554-55	125C14400RODXII/1554-105

		1-1/2-6 STEEL PLAIN	1-1/2-6 STEEL ZINC	1-1/2-6 STEEL H.D.G.	1-1/2-6 STEEL	1-1/2-6 STEEL H.D.G.	1-1/2-6 STEEL PLAIN
1-1/2-6	LENGTH "	F1554-GR36	F1554-GR36	F1554-GR36	PLAIN F1554-GR55	F1554-GR55	F1554-GR105
,	36" (3 FT)	150C3600RODXU/F1554-36	-	150C3600RODXG/F1554-36	150C3600RODXU/F1554-55	-	
	144" (12 FT)	-	-	150C14400RODXG/F1554-36	-	-	-





ASTM F1554 Anchor Bolts [Grade 36, Grade 55, Grade 105]

Daily delivery to most areas of San Diego Cty

ASTM A193-B7

125,000 psi

ASTM A193-B7 High Temp/ High Pressure

1/4-20		1/4-20 PLAIN	1/4-20 ZINC	1/4-20 H.D.G.
1/120	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	25C3600RODXU/A193-B7	-	-
	144" (12 FT)	25C14400RODXU/A193-B7	-	-

1/4-28		1/4-28 PLAIN	1/4-28 ZINC	1/4-28 H.D.G.
1/4-20	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	25F3600RODXU/A193-B7	-	-

5/16-18		5/16-18 PLAIN	5/16-18 ZINC	5/16-18 H.D.G.
-,	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	31C3600RODXU/A193-B7	-	-
	72" (6 FT)	31C7200RODXU/A193-B7	-	-
	144" (12 FT)	31C14400RODXU/A193-B7	-	-

5/16-24		5/16-24 PLAIN	5/16-24 ZINC	5/16-24 H.D.G.
,	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	31F3600RODXU/A193-B7	-	-
	72" (6 FT)	31F7200RODXU/A193-B7	-	-

3/8-16		3/8-16 PLAIN	3/8-16 ZINC	3/8-16 H.D.G.
-,	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	37C3600RODXU/A193-B7	-	-
	72" (6 FT)	37C7200RODXU/A193-B7	-	-
	144" (12 FT)	-	-	37C14400RODXG/A193-B7-D

3/8-24		3/8-24 PLAIN	3/8-24 ZINC	3/8-24 H.D.G.	
0,021	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7	
	36" (3 FT)	37F3600RODXU/A193-B7	-	-	_

7/16-14		7/16-14 PLAIN	7/16-14 ZINC	7/16-14 H.D.G.
-,	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	43C3600RODXU/A193-B7	-	-
	72" (6 FT)	43C7200RODXU/A193-B7	-	-
	144" (12 FT)	43C14400RODXU/A193-B7	-	-

7/16-20		7/16-20 PLAIN	7/16-20 ZINC	7/16-20 H.D.G.
,	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	43F3600RODXU/A193-B7	-	-
	72" (6 FT)	43F7200RODXU/A193-B7	-	-
	120" (10 FT)	43F12000RODXU/A193-B7	-	-
	144" (12 FT)	43F14400RODXU/A193-B7	-	-

1/2-13		1/2-13 PLAIN	1/2-13 ZINC	1/2-13 H.D.G.
_/	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	50C3600RODXU/A193-B7	50C3600RODXZ/A193-B7	=
	72" (6 FT)	50C7200RODXU/A193-B7	-	-
	120" (10 FT)	50C12000RODXU/A193-B7	-	-
	144" (12 FT)	50C14400RODXU/A193-B7	-	-

1/2-20	400,000,000	1/2-20 PLAIN	1/2-20 ZINC	1/2-20 H.D.G.
_/	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	50F3600RODXU/A193-B7	-	-
	72" (6 FT)	50F7200RODXU/A193-B7	-	-
	144" (12 FT)	50F14400RODXU/A193-B7	-	

9/16-12		9/16-12 PLAIN	9/16-12 ZINC	9/16-12 H.D.G.
3/10-12	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	56C3600RODXII/A193-B7		

9/16-18		9/16-18 PLAIN	9/16-18 ZINC	9/16-18 H.D.G.	Ī
,	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7	
	36" (3 FT)	56F3600RODXU/A193-B7	-	-	

	5/8-11 PLAIN	5/8-11 ZINC	5/8-11 H.D.G.
LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
36" (3 FT)	62C3600RODXU/A193-B7		-
72" (6 FT)	62C7200RODXU/A193-B7	-	-
120" (10 FT)	62C12000RODXU/A193-B7	-	-
144" (12 FT)	62C14400RODXU/A193-B7	٠	-
	36" (3 FT) 72" (6 FT) 120" (10 FT)	LENGTH " ASTM A193-B7 36" (3 FT) 62C3600RODXU/A193-B7 72" (6 FT) 62C7200RODXU/A193-B7 120" (10 FT) 62C12000RODXU/A193-B7	LENGTH " ASTM A193-B7 ASTM A193-B7 36" (3 FT) 62C3600RODXU/A193-B7 - 7,2" (6 FT) 62C7200RODXU/A193-B7 - 120" (10 FT) 62C12000RODXU/A193-B7 -

5/8-18		5/8-18 PLAIN	5/8-18 ZINC	5/8-18 H.D.G.
3/ 0-10	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	62F3600RODXU/A193-B7		-
	72" (6 FT)	62F7200RODXU/A193-B7		-
	144" (12 FT)	62F14400RODXU/A193-B7	•	-



Threaded Rod

ASTM A193-B7

125,000 psi

ASTM A193-B7 High Temp/ High Pressure

3/4-10		3/4-10 PLAIN	3/4-10 ZINC	3/4-10 H.D.G.
,	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	75C3600RODXU/A193-B7	-	-
	72" (6 FT)	75C7200RODXU/A193-B7	-	-
	120" (10 FT)	75C12000RODXU/A193-B7	-	-
	144" (12 FT)	75C14400RODXU/A193-B7	-	-

3/4-16		3/4-16 PLAIN	3/4-16 ZINC	3/4-16 H.D.G.
0/ 1 =0	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	75F3600RODXU/A193-B7	-	-
	144" (12 FT)	75F14400RODXU/A193-B7	-	-

7/8-9		7/8-9 PLAIN	7/8-9 ZINC	7/8-9 H.D.G.
-/	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	87C3600RODXU/A193-B7	-	-
	72" (6 FT)	87C7200RODXU/A193-B7	-	-
	1 4 4 U /12 FT\	07C14400DODVII/A102 D7		

7/8-14		7/8-14 PLAIN	7/8-14 ZINC	7/8-14 H.D.G.
1/0-14	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	87F3600RODXU/A193-B7	-	-

1" - 8	LENGTH "	1"-8 PLAIN ASTM A193-B7	1"-8 ZINC ASTM A193-B7	1"-8 H.D.G. ASTM A193-B7
	36" (3 FT)	100C3600RODXU/A193-B7	-	-
	72" (6 FT)	100C7200RODXU/A193-B7	- 1	-
	120" (10 FT)	100C12000RODXU/A193-B7	-	-
	144" (12 FT)	100C14400RODXU/A193-B7	-	100C14400RODXG/A193-B7

1" - 14		1"-14 PLAIN	1"-14 ZINC	1"-14 H.D.G.
1 . 14	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	100F3600RODXU/A193-B7		-
	144" (12 FT)	100F14400RODXU/A193-B7	-:	-

1-1/8 - 7		1-1/8-7 PLAIN	1-1/8-7 ZINC	1-1/8-7 H.D.G.
= =/ 0 :	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	112C3600RODXU/A193-B7		-
	144" (12 FT)	112C14400RODXU/A193-B7	-	

1-1/8 - 12		1-1/8-12 PLAIN	1-1/8-12 ZINC	1-1/8-12 H.D.G.
1-1/0-12	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	4 4 4 11 (4 0 5 7)	4405444000000001/11/4400 07		

1-1/4 - 7		1-1/4-7 PLAIN	1-1/4-7 ZINC	1-1/4-7 H.D.G.
/ -	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	125C3600RODXU/A193-B7	= 1	-
	72" (6 FT)	125C7200RODXU/A193-B7		-
	144" (12 FT)	125C14400RODXU/A193-B7	-	-

1-1/4 - 12	LENGTH "	1-1/4-12 PLAIN ASTM A193-B7	1-1/4-12 ZINC ASTM A193-B7	1-1/4-12 H.D.G. ASTM A193-B7
	72" (6 FT)	125F7200RODXU/A193-B7	-	-
	144" (12 FT)	125F14400RODXU/A193-B7	_	_

1-1/2 - 6		1-1/2-6 PLAIN	1-1/2-6 ZINC	1-1/2-6 H.D.G.
1-1/2-6	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	150C3600RODXU/A193-B7	-	-
	72" (6 FT)	150C7200RODXU/A193-B7	-	-
	144" (12 FT)	150C14400RODXU/A193-B7	-	-

1-1/2 - 12		1-1/2-12 PLAIN	1-1/2-12 ZINC	1-1/2-12 H.D.G.
1-1/2-12	LENGTH "	ASTM A193-B7	ASTM A193-B7	ASTM A193-B7
	36" (3 FT)	150F3600RODXU/A193-B7	-	-
	72" (6 FT)	150F7200RODXU/A193-B7	-	-
	144" (12 FT)	150F14400RODXU/A193-B7	-	-

STAINLESS

		ASTM F593-2017 70,000 psi	STAINLESS 18-8, 316, 304
0.50		2 FC (19 9)	2.56 (216)
2-56	LENGTH "	2-56 (18-8) STAINLESS	2-56 (316)
	36" (3 FT)		STAINLESS
	36 (3 F1)	2C3600RODS	-
4-40		4-40 (18-8)	4-40 (316)
7 70	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	4C3600RODS	-
5-40		5-40 (18-8)	5-40 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	5C3600RODS	-
		6.33 (10.0)	C 22 (21C)
6-32	LENGTH!	6-32 (18-8)	6-32 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	6C3600RODS	-
		8-32 (18-8)	8-32 (316)
8-32	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	8C3600RODS	JIAINLE33
	30 (311)	86300011003	
10.04		10-24 (18-8)	10-24 (316)
10-24	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	10C3600RODS	-
	00 (0.1.)		
10-32		10-32 (18-8)	10-32 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	10F3600RODS	-
	72" (6 FT)	10F7200RODS	-
1/4-20		1/4-20 (18-8)	1/4-20 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	25C3600RODS	25C3600ROD6
	72" (6 FT)	25C7200RODS	25C7200ROD6
	144" (12 FT)	25C14400RODS	25C14400ROD6
1/4-28		1/4-28 (18-8)	1/4-28 (316)
_/0	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	25F3600RODS	-
	· , , , ,		
5/16-18		5/16-18 (18-8)	5/16-18 (316)
,	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	31C3600RODS	31C3600ROD6
	72" (6 FT)	31C7200RODS	31C7200ROD6
	144" (12 FT)	31C14400RODS	31C14400ROD6
5/16-24		5/16-24 (18-8)	5/16-24 (316)
J/ 10 24	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	31F3600RODS	-

ABABA BOLT Commercial Hardware

THREADED ROD

STAINLESS

ASTM F593-2017 70,000 psi

ASTM F593-2017 STAINLESS 18-8, 316, 304

3/8-16

16		3/8-16 (18-8)	3/8-16 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	37C3600RODS	37C3600ROD6
	72" (6 FT)	37C7200RODS	37C7200ROD6
	144" (12 FT)	37C14400RODS	37C14400ROD6

3/8-24

	3/8-24 (18-8)	3/8-24 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	37F3600RODS	37F3600ROD6

7/16-14

	7/16-14 (18-8)	7/16-14 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	43C3600RODS	-
72" (6 FT)	43C7200RODS	-
144" (12 FT)	43C14400RODS	1

7/16-20

	7/16-20 (18-8)	7/16-20 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	43F3600RODS	ī
72" (6 FT)	43F7200RODS	•
144" (12 FT)	43F14400RODS	-

1/2-13

	1/2 12 /10 0		
	1/2-13 (18-8)		1/2-13 (316)
⊣"	STAINLESS		STAINLESS
	-		50C400ROD6S
	50C500RODS		-
"	50C550RODS		-
-T)	50C3600RODS		50C3600ROD6
-T)	50C7200RODS		50C7200ROD6
FT) 5	50C14400RODS	;	50C14400ROD6
	" -T)	+ " STAINLESS	+ " STAINLESS

1/2-20

	1/2-20 (18-8)	1/2-20 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	50F3600RODS	-
72" (6 FT)	50F7200RODS	ı

9/16-12

	9/16-12 (18-8)	9/16-12 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	56C3600RODS	-

9/16-18

	9/16-18 (18-8)	9/16-18 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	56F3600RODS	-

	5/8-11 (18-8)	5/8-11 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	62C3600RODS	62C3600ROD6
72" (6 FT)	62C7200RODS	62C7200ROD6
144" (12 FT)	62C14400RODS	62C14400ROD6

	5/8-18 (18-8)	5/8-18 (316)
LENGTH "	STAINLESS	STAINLESS
36" (3 FT)	62F3600RODS	-

STAINLESS

This in the second of the second of the second

ASTM F593-2017 STAINLESS 18-8, 316, 304

70,000 psi

3/4-10		3/4-10 (18-8)	3/4-10 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	75C3600RODS	75C3600ROD6
	72" (6 FT)	75C7200RODS	75C7200ROD6
	144" (12 FT)	75C14400RODS	75C14400ROD6

3/4-16		3/4-16 (18-8)	3/4-16 (316)
0, 1 =0	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	75F3600RODS	-

7/8-9		7/8-9 (18-8)	7/8-9 (316)
1/00	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	87C3600RODS	87C3600ROD6
	72" (6 FT)	87C7200RODS	87C7200ROD6
	144" (12 FT)	87C14400RODS	87C14400ROD6

7/8-14		7/8-14 (18-8)	7/8-14 (316)
1/0-14	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	87F3600RODS	-

1"-8		1"-8 (18-8)	1"-8 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	100C3600RODS	100C3600ROD6
	72" (6 FT)	100C7200RODS	100C7200ROD6
	144" (12 FT)	100C14400RODS	100C14400ROD6

1"-14		1"-14 (18-8)	1"-14 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	100F3600RODS	-
	72" (6 FT)	100F7200RODS	=

1-1/8-7		1-1/8-7 (18-8)	1-1/8-7 (316)
	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	112C3600RODS	-
	144" (12 FT)	112C14400RODS	112C14400ROD6

		1-1/4-7 (18-8)	1-1/4-7 (316)
1-1/4-7	LENGTH "	STAINLESS	STAINLESS
	36" (3 FT)	125C3600RODS	-
	72" (6 FT)	125C7200RODS	-
	144" (12 FT)	125C14400RODS	-

THREADED ROD



ACME THREAD

CALL FOR AVAILIBILITY



CALL FOR AVAILIBILITY



HASTELLOY, INCONEL, MONEL

ALLOY, DUPLEX, TITANIUM

EXOTICS

CALL FOR AVAILIBILITY



ASTM A193-B6

ASTM A193-B8

ASTM A193-B8M

CALL FOR AVAILIBILITY



METRIC SIZES

METRIC ROD IN STOCK

CALL FOR AVAILABILITY

